

BLANK PAGE



IS:7010-1973 REAFFIRMED

Indian Standard

SPECIFICATION FOR PIVOTS FOR MAGNETIC COMPASSES

UDC 744·342·032



© Copyright 1973

INDIAN STANDARDS INSTITUTION
MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG
NEW DELHI 110001



AMENDMENT NO. 1 APRIL 1987

TO

1S:7010-1973 SPECIFICATION FOR PIVOTS FOR MAGNETIC COMPASSES

(Page 4, clause 5.5) - Substitute the following for the existing clause:

'5.5 The materials used for all 4 types of pivots shall be non-magnetic.'

(EDC 36)

Reprography Unit, ISI, New Delhi, India

Indian Standard

SPECIFICATION FOR PIVOTS FOR MAGNETIC COMPASSES

Optical and Mathematical Instruments Sectional Committee, EDC 36

Chairman

DR C. S. RAO

Kailas, Frenchpet, Masulipatam

Members

Representing

SHRT A. ALVARES

All India Instrument Manufacturers and Dealers Association, Bombay

SHRI V. K. VABUDEVAN (Alternate) SHRI A. N. BHATTACHARYA

Ministry of Defence (R & D) Survey of India, Dehra Dun

SHRI I. CHATTERJEE CHIEF HYDROGRAPHER (NAVY)

Naval Headquarters DEPUTY DIRECTOR, STANDARDS Research, Designs and Standards Organization

(Ministry of Railways), Lucknow

ASSISTANT DIRECTOR, STAND-ARDS (TRACK) (Alternate)

INSTRUMENTS Ministry of Defence (R & D)

DIRECTOR, INSTRUMENTS RESEARCH & DEVELOPMENT

ESTABLISHMENT SHRIS. S. DHARMAYYA (Alternate)

SHRI S. K. GAUTAM

Quality Marked Goods Manufacturers' Co-operative Association Ltd, Roorkee

SHRI P. L. BHARDWAJ (Alternate)

Directorate General, Ordnance Factories, Ministry

SHRIS. K. GHOSE

of Defence National Test House, Calcutta

SHRI A. GHOSH SHRI P. C. JAIN SHRI RAM PRASAD (Alternate)

National Physical Laboratory (CSIR), New Delhi

SHRI D. D. KHOSLA COL K. L. KHOSLA

Directorate of Industries, Government of Haryana, Chandigarh

COL N. P. MANARTAL LT-COL H. LAL (Alternate) SHRI B. R. MANKHAND DR M. V. R. K. MURTY

The Institution of Surveyors, New Delhi Ministry of Defence (DGI)

LT-COL B. PAPANNA DR J. PRASAD

The Koh-I-Noor (India) Private Ltd; Varanasi Department of Atomic Energy, Bombay Army Headquarters

Chandigarh

Central Scientific Instruments Organization (CSIR).

SHRI RAM SINGH (Afternate)

(Confinued on page 2)

Copyright 1973 INDIAN STANDARDS INSTITUTION

This publication is protected under the Indian Copyright Act (XIV of 1957) and reproduction in whole or in part by any means except with written permission of the publisher shall be deemed to be an infringement of copyright under the said Act.

IS: 7010-1973

(Continued from page 1)

Members

Representing

SHRI S. RAGHVIAH

Development Commissioner, Small Scale Industries. New Delhi

SHRI E. B. RAJDERKAR

Raj-Der-Kar & Co, Bombay

KUMARI SUBAS RAJDERKAR (Alternate)

SHRI K. N. RAMASWAMY

Directorate General of Technical Development, New Delhi

SHRI P. V. MAMMEN (Alternate)

SHRI C. NARAYANA RAO

The Andhra Scientific Co Ltd, Masulipatam

Dr I. Ramakrishna Rao

In personal capacity (Toshniwal Instruments and Engineering Co, 10A. Najafgarh Road. New Delhi 15)

PROF G. S. S. SARMA LT-COL G. S. SIHOTA Madras Institute of Technology, Madras Directorate General of Armed Forces Medical

Service, Ministry of Defence Central Public Works Department, New Delhi

SURVEYOR OF WORKS I [OFFICE SUPERINTENDING SURVEYOR OF WORKS (NDZ)] SHRI K. G. TORGAL

The National Instruments & Ophthalmic Glass Ltd,

SHRI A. GHOSH (Alternate) SHRI H. C. VERMA

Associated Instrument Manufacturers (India) Private Limited, New Delhi

SHRI K. G. PURANG (Alternate) SHRI S. M. RAZVI, Head (Mech Engg)

Director General, ISI (Ex-officio Member)

Secretary

Calcutta

SHRI S. P. ABBEY Assistant Director (Mech Engg), ISI

Materials and Components for Instruments Subcommittee, EDC 36:5

Convener

SHRI H. C. VERMA

Associated Instrument Manufacturers (India) Private Limited, New Delhi

Members

SHRI N. R. CHAKARABARTI

SHRI S. K. GHOSE

DR J. PRASAD

Ministry of Defence (R & D) Directorate General, Ordnance Factories, Ministry

LT-COL H. LAL SHRI H. N. DE (Alternate)

SHRIS. K. MUKHERJEE

Ministry of Defence (DGI)

of Defence

SHRI RAM PRASAD SHRIK. N. RAMASWAMY Precision Optics & Machineries (P) Ltd, Calcutta Central Scientific Instruments Organization (CSIR), Chandigarh

National Physical Laboratory (CSIR), New Delhi Directorate General of Technical Development, New Delhi

SHRI P. V. MAMMEN (Alternate)

Indian Standard

SPECIFICATION FOR PIVOTS FOR MAGNETIC COMPASSES

0. FOREWORD

- **0.1** This Indian Standard was adopted by the Indian Standards Institution on 21 June 1973, after the draft finalized by the Optical and Mathematical Instruments Sectional Committee had been approved by the Mechanical Engineering Division Council.
- **0.2** For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test or analysis, shall be rounded off in accordance with IS:2-1960*. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

1. SCOPE

- 1.1 This specification covers the requirements for pivots used for giving frictionless support to the magnetic needles in various types of compasses.
- 1.2 This specification does not cover special requirements.

2. TYPES

2.1 The pivots shall be of the following types:

Type A - Plain;

Type B — Plain and alloy tipped;

Type C - Screwed, slotted head; and

Type D - Screwed, slotted head and alloy tipped.

3. MATERIAL AND HARDNESS

3.1 The material for the Types A and C pivots shall be tool steel conforming to IS: 1570-1961†.

^{*}Rules for rounding off numerical values (revised).

[†]Schedules for wrought steels for general engineering purposes.

IS: 7010 - 1973

- 3.2 The material for Types B and D pivots shall be as follows:
 - Shank -- Brass conforming to IS: 319-1968*.
 - Tips Osmium-iridium, iridium or tungsten carbide conforming to IS:7010-1973.
- 3.3 In case of tool steel, Types A and C pivots, hardness of the tips shall not be less than 700 HV (micro hardness); and for alloy tips, that is, Types B and D, the hardness shall be 1400 HV (micro hardness), Min. Pivots of Types A and C shall be properly tampered after hardening.

4. DIMENSIONS

4.1 The shapes and dimensions of the pivots shall be as given in Table 1.

5. GENERAL REQUIREMENTS

- 5.1 The tip of the pivots shall be concentric with the axis of the pivots and shall be spherical.
- 5.2 The tips shall be highly polished, and hardened.
- 5.3 Dimensions of the tips and the shank portion shall be maintained.
- 5.4 In case of Types B and D pivots, there shall not be any holes, cracks, and pitting marks or any other deformities between points of tip and shank at the joint.
- 5.5 All materials used for Types B and D pivots shall be nonmagnetic.

6. DESIGNATION

6.1 The pivot shall be designated by its name, type, length and the number of this standard.

Example:

A pivot of Type A, having a length l=25 mm shall be designated as:

Pivot A 25 IS: 7010-1973.

7. WORKMANSHIP AND FINISH

7.1 All surfaces of the pivots shall be smooth. Finish of the tips by plating is not recommended.

8. PACKING AND MARKING


8.1 The packing shall be such that the pivots do not get rusted and the tips are adequately protected from damage. This shall be done by greasing the pivots properly and then piercing them into a suitable soft material of sufficient thickness.

^{*}Specification for free-cutting brass rods and sections (second revision).

TABLE 1 DIMENSIONS FOR PIVOTS

(Clause 4.1)

All dimensions in millimetres.



Note — Other dimensions and details of Type B and Type D are the same as for Type A and Type C respectively.

Түре	l à	/1	ď	R
A and B	12·5	6·25	1·5	0·04
	25·0	18·75	3·0	0·1
C and D	10·5	3·2	M2·2	0·04
	12·5	3·3	M2·2	0·04
	25·0	5·0	M3	0·1

IS: 7010 - 1973

- 8.2 The pivots shall be packed parallel with one another and so arranged that any one may be removed from the package without disturbing others.
- 8.3 Each packet of the pivots shall be wrapped and sealed to prevent the ingress of dampness or dust.
- 8.4 Each packet of pivots shall be suitably marked with the designation for proper identification.
- 8.4.1 The packets of pivots may also be marked with the ISI Certification Mark.

Note — The use of the ISI Certification Mark is governed by the provisions of the Indian Standards Institution (Certification Marks) Act, and Rules and Regulations made thereunder. The ISI Mark on products covered by an Indian Standard conveys the assurance that they have been produced to comply with the requirements of that standard under a well-defined system of inspection, testing and quality control which is devised and supervised by ISI and operated by the producer. ISI marked products are also continuously checked by ISI for conformity to that standard as a further safeguard. Details of conditions under which a licence for the use of the ISI Certification Mark may be granted to manufacturers or processors, may be obtained from the Indian Standards Institution.

INDIAN STANDARDS ON

SURVEYING INSTRUMENTS

IS:	and the second s
1492-1959	Metric surveying chains
1632-1960	Bubbles
1764-1961	Trough compass
1779-1961	4-Metre, levelling staff, folding type
1842-1961	Surveying chains pins (arrows)
1955-1961	Prismatic compass, liquid
1957-1961	Prismatic compasses, non-liquid
2288-1963	Ranging rods
2539-1963	Plane tables
2976-1964	Optical theodolite
2988-1965	Vernier theodolite
4380-1967	Abney level
4590-1967	Engineer's level
5146-1969	Sounding sextant
5706-1970	Spirit levels for use in precision engineering
5928-1970	Tangent clinometer

INDIAN STANDARDS INSTITUTION	
Manak Bhavan, 9 Bahadur Shah Zafar Marg, NEW	DELHI 110001
Telephone: 27 01 31 (20 lines)	Telegrams

Branch Offices:	Telephone
Sadhna ', Nurmohamed Shaikh Marg, Khanpur, AHMEDABAD 380001	2 03 91
f Block, Unity Bldg, Narasimharaja Square, BANGALORE 560002	27649
534 Sardar Vallabhbhai Patel Road, BOMBAY 400007	35 69 44
5 Chowringhee Approach, CALCUTTA 700013	23-08 02
5-9-201/2-A (First Floor), Chirag Ali Lane, HYDERABAD 500001	3 44 35
117/418 B Sarvodaya Nagar, KANPUR 208005	82 72
54 General Patters Road, MADRAS 600002	8 72 78

: Manaksanstha